




EV Charging Point

Single Phase, External Pro Earth 7.3kW Charger

EVIQ-7 PRO



Features

- **Compact design**
- **Free app**
- **Full protection**
Full electrical protection, over/under temperature protection, etc
- **Stable**
IP65 protection grade, usable in harsh & salt/mist environments
- **Intelligent**
Intelligent power adjustment, emergency stop, Wifi/APP/ethernet monitoring
- **Easy to install**
Wall-mounting or pole-mounting optional
- **Solar Compatible**

Specification

Input & Output

Voltage	230V AC
Input Frequency	50/60Hz
Output Voltage	230V AC
Max Output Power	7.3kW
Max Output Current	32A
Charging Interface	IEC 62196-2, Type 2
Connection	Untethered

Protection

Overload Protection	Yes
Short Circuit Protection	Yes
Earth Leakage Protection	Yes
Over-temp Protection	Yes

Function & Accessory

Ethernet/WIFI	Yes/Yes
RCD	Type A + 6mA DC fault current protection (Equivalent to Type B)
Supported Payment	RFID(Opt)
LED Indicator Light	Yes
Emergency Stop Button	Yes
Intelligent Power Adjustment	Opt

Working Environment

Protection Degree	IP65
Operating Temperature	-20°C ~+50°C
Standby Power Consumption	<8W

Mechanical

Dimensions (w/h/d)	240 x 380 x 164mm
Weight	<7Kg
Wall-mounting Bracket/	Yes/
Ground-mounting Pole	Opt

Contact us for more information

sara.mason-parker@gl-e.uk • ryan.shemwell@gl-e.uk • 01905 610200

